SONY
make.believe

The XS-GS120L SVC subwoofer cone is constructed using a Mica Reinforced Cellular composite for reduced weight and increase rigidity, delivering deep bass response.

Bullets

- 12" Single Voice Coil subwoofer
- Mica Reinforced Cellular Glass Fiber Composite Cone
- Single 4 Ohm voicecoil
- Gold plated 5-way binding posts
- 1300W Peak (380W Rated)
- 500 Watts CEA 2031 RMS Power
- 3 year warranty

Features

Subwoofer design

The XS-GS120L SVC subwoofer cone is constructed using a Mica Reinforced Cellular composite for reduced weight and increase rigidity, delivering deep bass response. The 5-way gold plated binding post provide secure wire connections for high power handling.

High energy magnets

The XS-GS120L woofer uses a powerful, high energy Ferrite magnet to control cone travel and deliver big power handling.

Power handling

The XS-GS120L subwoofer is rated for 380 Watts, 500 Watts RMS (CEA 2031 rated) and can handle peak power of 1300 Watts.

Warranty

The Sony® GS series subwoofers come with a 3 year warranty.

Specifications

Audio	
Frequency Response	30 - 1000 Hz
Impedance	4 Ohms
Sensitivity (db)	84 +/-2dB (1W, 1m)
General	
Magnet	Ferrite
Material	Mica Reinforced Cellullar Glass Fiber Cone
Power	
Power Handling Capacity	500 Watts CEA2031 RMS
Rated Input	380 Watts
Weights and Measurements	
Depth (Approx.)	5 1/2"
Diameter (Approx.)	12"
Dimensions (Approx.)	Woofer 12" (30cm) Cone
Dimensions (Approx) Depth	5 1/2"

SONY
make.believe

Mounting Dimensions (Approx.)	11" diameter
Weight (Approx.)	11 lbs.

Supplied Accessories

Supplied Accessories	Parts for Installation

© 2011 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony is a trademark of Sony. All other trademarks are the property of their respective owners. Features and specifications are subject to change without notice. Updated: March 9, 2012